

PD05924AM

CLAIM AMENDMENTS

1. (currently amended) A method for identifying [a type of impairment] impairments in a [system communicating a] digitally modulated signal comprising the steps of:

obtaining soft decision data derived from the digitally modulated signal;

applying [an] a plurality of impairment [mask] masks to the soft decision data, each impairment mask associated with a different impairment type;

determining a subset of the soft decision data that occur within [the] each impairment mask; [and]

calculating a correlation weight based on [the] each subset; and

based on the correlation weights, determining a likelihood that a particular impairment type is affecting the digitally modulated signal.

2. (original) The method of claim 1 further comprising the step of:
normalizing the soft decision data.

3. (currently amended) The method of claim 2 wherein the impairment [mask is] masks are selected from a group consisting of:

a phase noise impairment mask;

a continuous wave noise impairment mask;

a signal reflection impairment mask;

an I/Q imbalance impairment mask;

a compression impairment mask;

an amplitude-modulation-to-phase-modulation impairment mask; and

a composite phase noise and continuous wave noise impairment mask.

4. (original) The method of claim 2 further comprising the step of:
providing a three-dimensional presentation of a distribution of the soft decision data over time.

PD05924AM

5. (currently amended) The method of claim 1 further comprising the step of:
providing information descriptive of a distribution of occurrences of soft decision
data within specific regions of the impairment [mask] masks.
6. (canceled)
7. (currently amended) A method for detecting impairment of a digital signal
comprising the steps of:
calculating a first correlation weight for a first symbol-level impairment mask;
storing the first correlation weight;
calculating a second correlation weight for a first constellation-level impairment
mask, the first constellation-level impairment mask operative to detect a different
impairment type than the first symbol-level impairment mask;
storing the second correlation weight; and
calculating an overall correlation weight based on the first correlation weight and
the second correlation weight.
8. (original) The method of claim 7 further comprising the steps of:
calculating a third correlation weight for a second symbol-level
impairment mask;
storing the third correlation weight;
calculating a fourth correlation weight for a second constellation-level impairment
mask; and
storing the fourth correlation weight, wherein the step of calculating the overall
correlation weight based on the first correlation weight and the second correlation weight
further includes the step of calculating the overall correlation weight based on the first
correlation weight, the second correlation weight, the third correlation weight, and the
fourth correlation weight.
9. (original) The method of claim 8 further comprising the step of:

PD05924AM

measuring a quality of the digital signal.

10. (original) The method of claim 9 wherein the step of measuring a quality of the digital signal further comprises the step of:
checking a signal-to-noise ratio.

11. (original) The method of claim 7 wherein the first symbol-level impairment mask is selected from a symbol-level impairment mask group consisting of:
a phase noise impairment mask;
a continuous wave noise impairment mask;
a composite phase noise and continuous wave noise impairment mask; and
a signal reflection impairment mask,
and wherein the first constellation-level impairment mask is selected from a constellation-level impairment trade group consisting of:
an I/Q imbalance impairment mask;
a compression impairment mask; and
an amplitude-modulation-to-phase-modulation impairment mask.

12. (currently amended) A digital receiving apparatus comprising:
a receiver responsive to a digitally modulated signal to perform conversion of the digitally modulated signal to soft decision data; and
an impairment correlator operatively coupled to the receiver and responsive to the soft decision data to correlate a plurality of different types of impairments [impairment] of the digitally modulated signal.

13. (currently amended) The digital receiving apparatus of claim 12 further comprising:
a memory device operatively coupled to the impairment correlator to store a plurality of impairment masks associated with the plurality of different types of impairments.

PD05924AM

14. (original) The digital receiving apparatus of claim 13 further comprising:
an error vector magnitude mask subsystem operatively coupled to the receiver and responsive to the soft decision data to assess a quality of the soft decision data.
15. (original) The digital receiving apparatus of claim 14 wherein the error vector magnitude mask subsystem further comprises:
a SNR analyzer operatively coupled to the receiver and responsive to the soft decision data; and
an error vector magnitude mask memory device operatively coupled to the SNR analyzer to provide an error vector magnitude mask to the SNR analyzer.
16. (original) The digital receiving apparatus of claim 13 further comprising a system controller operatively coupled to the impairment correlator to receive a correlation weight from the impairment correlator and to effect control of the digital receiving apparatus in response to the correlation weight.
17. (original) The digital receiving apparatus of claim 13 further comprising a system controller operatively coupled to the impairment correlator to receive a correlation weight from the impairment correlator and to effect control of a transmitter in response to the correlation weight, the transmitter operatively coupled to the receiver to provide the digitally modulated signal to the receiver.
18. (original) The digital receiving apparatus of claim 13 further comprising a system controller operatively coupled to the impairment correlator to receive a correlation weight from the impairment correlator and to effect control of a medium in response to the correlation weight, the medium operatively coupled to the receiver to convey the digitally modulated signal to the receiver.
19. (currently amended) A cable modem comprising:
a cable modem receiver responsive to a downstream signal to perform conversion of the downstream signal to soft decision data; and

PD05924AM

an impairment correlator operatively coupled to the cable modem receiver and responsive to the soft decision data to correlate a plurality of different types of impairments [impairment] of the downstream signal.

20. (currently amended) The cable modem of claim 19 further comprising:
a memory device operatively coupled to the impairment correlator to store a plurality of impairment masks associated with the plurality of different types of impairments.

21. (original) The cable modem of claim 20 further comprising:
a cable modem transmitter operatively coupled to the impairment correlator to transmit a correlation weight from the impairment correlator to a cable modem termination system.

22. (original) The cable modem of claim 20 further comprising an error vector magnitude mask subsystem operatively coupled to the cable modem receiver and responsive to the soft decision data to assess a quality of the soft decision data.

23. (original) The cable modem of claim 22 wherein the error vector magnitude mask subsystem further comprises:
a SNR analyzer operatively coupled to the cable modem receiver and responsive to the soft decision data; and
an error vector magnitude mask memory device operatively coupled to the SNR analyzer to provide an error vector magnitude mask to the SNR analyzer.

24. (currently amended) A cable modem termination system comprising:
a cable modem termination system receiver responsive to an upstream signal to perform conversion of the upstream signal to soft decision data; and
an impairment correlator operatively coupled to the cable modem termination system receiver to correlate a plurality of different types of impairments [impairment] of the upstream signal.

PD05924AM

25. (currently amended) The cable modem termination system of claim 24 further comprising: a memory device operatively coupled to the impairment correlator to store a plurality of impairment masks associated with the plurality of different types of impairments.

26. (original) The cable modem termination system of claim 25 further comprising:

a network management system operatively coupled to the impairment correlator to provide a corrective control signal to a cable modem transmitting the upstream signal.

27. (original) The cable modem termination system of claim 25 further comprising:

an error vector magnitude mask subsystem operatively coupled to the cable modem termination system receiver and responsive to the soft decision data to assess a quality of the soft decision data.

28. (original) The cable modem termination system of claim 27 wherein the error vector magnitude mask subsystem further comprises:

a SNR analyzer operatively coupled to the cable modem termination system receiver and responsive to the soft decision data; and

an error vector magnitude, mask memory device operatively coupled to the M analyzer to provide an error vector magnitude mask to the SNR analyzer.

29. (currently amended) A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform method steps for identifying impairment of a digitally modulated signal received by the machine, the method steps comprising:

applying [an] a plurality of impairment [mask] masks to soft decision data derived from the digitally modulated signal, each impairment mask associated with a different impairment type;

PD05924AM

determining a subset of the soft decision data that occur within [the] each impairment mask; [and]
 calculating a correlation weight based on [the] each subset; and
based on the correlation weights, determining a likelihood that a particular impairment type is affecting the digitally modulated signal.

30. (original) The program storage device of claim 29 wherein the method steps further comprise:

normalizing the soft decision data.

31. (currently amended) The program storage device of claim 30 wherein the impairment [mask is] masks are selected from a group consisting of:

a phase noise impairment mask;
 a continuous wave noise impairment mask;
 a signal reflection impairment mask;
 an I/Q imbalance impairment mask;
 a compression impairment mask;
 an amplitude-modulation-to-phase-modulation impairment mask; and
 a composite phase noise and continuous wave noise impairment mask.

32. (original) The program storage device of claim 29 wherein the method steps further comprise:

providing a three-dimensional presentation of a distribution of the soft decision data over time.

33. (currently amended) The program storage device of claim 29 wherein the method steps further comprise:

providing information descriptive of a distribution of occurrences of soft decision data within specific regions of the impairment [mask] masks.

PD05924AM

34. (canceled)

35. (currently amended) A method for identifying a type of impairment in a system communicating a digitally modulated signal comprising the steps of:

obtaining soft decision data derived from the digitally modulated signal; [and]

performing ratio analysis on the soft decision data; and

reporting a likelihood that a plurality of types of impairments corresponding to the ratio analysis are affecting the digitally modulated signal.

36. (original) The method of claim 35 further comprising the step of:
providing a three-dimensional presentation of a distribution of the soft decision data over time.

37. (canceled)

38. (currently amended) A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform method steps for identifying impairment of a digitally modulated signal received by the machine, the method steps comprising:

deriving soft decision data from the digitally modulated signal; [and]

performing ratio analysis on the soft decision data derived from the digitally modulated signal ; and

reporting a likelihood that a plurality of types of impairments corresponding to the ratio analysis are affecting the digitally modulated signal.

39. (original) The program storage device of claim 38 wherein the method steps further comprise:

providing a three-dimensional presentation of a distribution of the soft decision data over time.

40. (canceled)

PD05924AM

41. (canceled)

42. (canceled)

43. (canceled)

44. (canceled)

45. (canceled)

46. (canceled)

*Al
Cont.*